| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|-----------------------|--------------------------|-----------------------|
| SECTION 1. PRODUCT AN | D COMPANY IDENTIFICATION | |

| Material name | : | Renown® Chalkboard & Whiteboard Cleaner | | | |
|------------------------------------|---|---|--|--|--|
| Material number | : | A00101 | | | |
| Manufacturer or supplier's details | | | | | |
| Company | : | Interline Brands | | | |
| Address | : | 701 San Marco Blvd. Jacksonville, FL 32207 | | | |
| Telephone | : | 1-866-412-6726 | | | |

| Emergency telephone nu | mbei | rs |
|-----------------------------------|------|-------------------------|
| For SDS Information | : | 1-866-412-6726 |
| For a Medical Emergency | : | 1-800-424-9300 |
| For a Transportation Emergency | : | Chemtrec 1-800-424-9300 |

Note: Products labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations: The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | Aerosol containing a liquefied gas |
|------------|------------------------------------|
| Colour | white |
| Odour | characteristic |

| Gases under pressure | : Liquefied gas |
|--------------------------|--|
| GHS Label element | |
| Hazard pictograms | |
| Signal word | : Warning |
| Hazard statements | : H280 Contains gas under pressure; may explode if heated. |
| Precautionary statements | : Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place. |

Potential Health Effects

Renown® Chalkboard & Whiteboard Cleaner (REN05000-AM / 880253

| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|------------------|---|--|
| Carcinogenicity: | | |
| IARC | No component of this product preser equal to 0.1% is identified as probab human carcinogen by IARC. | |
| ACGIH | Confirmed animal carcinogen with ur humans ethanol 2-butoxyethanol | nknown relevance to 64-17-5 111-76-2 |
| OSHA | No component of this product preser equal to 0.1% is identified as a carcin carcinogen by OSHA. | nt at levels greater than or |
| NTP | No component of this product preser equal to 0.1% is identified as a know by NTP. | |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical Name | CAS-No. | Concentration [%] |
|-----------------|----------|-------------------|
| propane | 74-98-6 | >= 1 - < 5 |
| ethanol | 64-17-5 | >= 1 - < 5 |
| butane | 106-97-8 | >= 1 - < 5 |
| 2-butoxyethanol | 111-76-2 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

| General advice | Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance. | |
|-------------------------|---|-----|
| If inhaled | If inhaled, remove to fresh air. If symptoms persist, call a physician. | |
| In case of skin contact | In case of contact, immediately flush skin with plenty of wate for at least 15 minutes while removing contaminated clothin and shoes. Get medical attention if irritation develops and persists. | |
| In case of eye contact | Rinse immediately with plenty of water for at least 15 minute Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. | ЭS. |
| If swallowed | DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. | |

Version 1.0Revision Date 04/27/2015Print Date 05/28/2015

SECTION 5. FIREFIGHTING MEASURES

| Suitable extinguishing media | : Dry chemical Carbon dioxide (CO2) Foam |
|---|---|
| Unsuitable extinguishing media | : High volume water jet |
| Hazardous combustion products Specific extinguishing methods | Carbon dioxide (CO2) Carbon monoxide Smoke Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Standard procedure for chemical fires. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
|---|---|--|
| Environmental precautions | : | Prevent further leakage or spillage if safe to do so. |
| Methods and materials for containment and cleaning up | : | Sweep up or vacuum up spillage and collect in suitable container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). |

SECTION 7. HANDLING AND STORAGE

| Advice on safe handling | oplication area. | J |
|-----------------------------|--|--|
| Conditions for safe storage | xposure and temperat r throw into fire even a ed-hot objects. bserve label precaution eep in a dry, cool and | well-ventilated place. working materials must comply with |
| Materials to avoid | trong oxidizing agents | 3 |

Renown® Chalkboard & Whiteboard Cleaner (REN05000-AM / 880253

Version 1.0

Revision Date 04/27/2015

Print Date 05/28/2015

Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------|----------|-------------------------------------|---|-----------|
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA P0 |
| ethanol | 64-17-5 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA P0 |
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 800 ppm 1,900 mg/m3 | OSHA P0 |
| 2-butoxyethanol | 111-76-2 | TWA | 20 ppm | ACGIH |
| | | TWA | 5 ppm 24 mg/m3 | NIOSH REL |
| | | TWA | 50 ppm 240 mg/m3 | OSHA Z-1 |
| | | TWA | 25 ppm 120 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Component | CAS-No. | Control | Biological | Sampling | Permissible | Basis |
|---------------------|----------|----------------------------|------------|--|---------------|-----------|
| | | parameters | specimen | time | concentration | |
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic acid (BAA) | Urine | End of shift (As soon as possible after exposure ceases) | 200 mg/g | ACGIH BEI |
| Remarks: Creatinine | | | | , | | |

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. In the case of dust or aerosol formation use respirator with an approved filter.

| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|----------------------------|--|-----------------------|
| Hand protection Remarks | : The suitability for a specific workpla with the producers of the protective | |
| Eye protection | : Safety glasses | |
| Skin and body protection | : impervious clothing Choose body protection according concentration of the dangerous sub | |
| Hygiene measures | : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at t | he end of workday. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | : | Aerosol containing a liquefied gas |
|--|---|------------------------------------|
| Colour | : | white |
| Odour | : | characteristic |
| Odour Threshold | : | no data available |
| рН | : | 10.5 - 11.5 |
| Melting point/freezing point | : | no data available |
| Boiling point | : | no data available |
| Flash point | : | |
| | | no data available |
| Evaporation rate | : | no data available |
| Flammability (solid, gas) | : | The product is not flammable. |
| | | |
| Upper explosion limit | : | no data available |
| Lower explosion limit | : | no data available |
| Vapour pressure | : | 482.6 hPa (21 °C) |
| 5 1 <i>2</i> | | |
| Relative vapour density | : | no data available |
| Relative density | : | no data available |
| Density | : | 0.985 g/cm3 |
| Solubility(ies) | | |
| Water solubility | : | soluble |
| Partition coefficient: n- octanol/water | : | no data available |
| Auto-ignition temperature | : | not determined |
| Thermal decomposition | : | no data available |
| Viscosity | | |

| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|----------------------|--------------------------|-----------------------|
| Viscosity, kinematic | : not determined | |
| Heat of combustion | : 3.08 kJ/g | |

SECTION 10. STABILITY AND REACTIVITY

| Reactivity | : Stable |
|------------------------------------|---|
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. |
| reactions | Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | : Carbon dioxide (CO2) Carbon monoxide |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

| Product: | |
|--|---|
| Acute oral toxicity | : Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : Acute toxicity estimate : > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method |
| Acute dermal toxicity | : Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method |
| Components: | |
| propane: Acute inhalation toxicity | : LC50 mouse: 1,237 mg/l Exposure time: 2 h |
| | LC50 rat: 658 mg/l Exposure time: 4 h |
| | LC50 rat: 1,355 mg/l |

| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|---|--|-----------------------|
| ethanol: Acute oral toxicity | : LD50 Oral rat: 7,060 mg/kg | |
| Acute inhalation toxicity | : LC50 rat: 124.7 mg/l Exposure time: 4 h | |
| butane: Acute inhalation toxicity | : LC50 mouse: 1,237 mg/l Exposure time: 2 h | |

LC50 rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

propane: ethanol: butane: 2-butoxyethanol:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

 Version 1.0
 Revision Date 04/27/2015
 Print Date 05/28/2015

 SECTION 12. ECOLOGICAL INFORMATION
 Ecotoxicity

 no data available
 Persistence and degradability

 no data available
 Bioaccumulative potential

 Product:
 Product:

| Partition coefficient: n- octanol/water <u>Components:</u> butane : Partition coefficient: n- | Remarks: no data availablePow: 2.89 |
|---|--|
| octanol/water | |
| Mobility in soil | |
| no data available | |
| Other adverse effects | |
| no data available <u>Product:</u> | |
| Regulation | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances |
| Remarks | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : no data available |

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | |
|------------------------|--|
| Waste from residues | Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations. |
| Contaminated packaging | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. |

Renown® Chalkboard & Whiteboard Cleaner (REN05000-AM / 880253

| Version 1.0 Revision Date 04/27/2015 | |
|--------------------------------------|--|
|--------------------------------------|--|

Print Date 05/28/2015

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------------|----------|-----------------------|--------------------------------|
| 2,2'-iminodiethanol | 111-42-2 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

| SARA 311/312 Hazards | : Sudden Release of Pressure Hazard | |
|---|---|--|
| SARA 302 | : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. | |
| SARA 313 | : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. | |
| California Prop 65 2,2'-iminodieti | WARNING! This product contains a chemical known to the State of California to cause cancer. nol 111-42-2 | |
| The components of this product are reported in the following inventories: | | |
| The components of this product are reported in the following inventories. | | |

TSCA On TSCA Inventory


Renown® Chalkboard & Whiteboard Cleaner (REN05000-AM / 880253

| Version 1.0 | Revision Date 04/27/2015 | Print Date 05/28/2015 |
|-------------|---|-----------------------|
| DSL | This product contains one or several components that are not on the | |
| | Canadian DSL nor NDSL. | |
| AICS | Not in compliance with the inventory | |
| NZIoC | Not in compliance with the inventory | |
| PICCS | Not in compliance with the inventory | |
| IECSC | Not in compliance with the inventory | |

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION



OSHA GHS Label Information:



We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Version 1.0 Revision Date 04/27/2015

Print Date 05/28/2015

1000801